WHAT IS CLAIMED IS:

10

15

- 1. A method of water analysis for detecting the presence of microorganisms in a water sample, comprising the step of staining the microorganisms with potassium permanganate (KMnO₄).
- 2. A method of water analysis for detecting the presence of microorganisms in a water sample, comprising the steps of:

providing a bio-membrane as a filter;

filtering out the microorganisms in the water sample, using the bio-membrane;

cultivating the microorganisms on the bio-membrane;

staining the microorganisms on the bio-membrane with potassium permanganate (KMnO₄);

rinsing the bio-membrane with purified deionized water, and

performing a colony count for readable microorganisms on the bio-membrane.

3. The method of water analysis according to claim 2, wherein the pore

5

10

15

size of the bio-membrane is about 0.3 µm in diameter.

- 4. The method of water analysis according to claim 2, wherein the water sample is filtered through the bio-membrane by a vacuum filtration technique.
- 5. The method of water analysis according to claim 2, wherein the microorganisms are cultivated on the bio-membrane at about 30°C, using 2 ml of nutrient solution.
- 6. The method of water analysis according to claim 2, wherein the concentration of KMnO₄ is about 0.02 M (mole per liter).
- 7. The method of water analysis according to claim 2, wherein the microorganisms on the bio-membrane are stained with KMnO₄ for about 10 to 30 seconds and then the bio-membrane is rinsed with purified deionized water.
- 8. A method of water analysis for separately detecting the presence of microorganisms in a plurality of water samples, comprising the steps of:
 - providing a plurality of bio-membranes as filters;

filtering out the microorganisms in each of the water samples, using a corresponding bio-membrane, separately;

5

10

15

cultivating the microorganisms on different bio-membranes for different time period;

staining the microorganisms on each of the bio-membranes with potassium permanganate (KMnO₄);

rinsing each of the bio-membranes with purified deionized water; and

performing a colony count for readable microorganisms on each of the bio-membranes.

- 9. The method of water analysis according to claim 8, wherein the pore size of the bio-membrane is about 0.3 µm in diameter.
- 10. The method of water analysis according to claim 8, wherein each of the water samples is filtered through a corresponding bio-membrane by a vacuum filtration technique.
- 11. The method of water analysis according to claim 8, wherein the microorganisms are cultivated on each of the bio-membranes at about 30°C, using 2 ml of nutrient solution.
- 12. The method of water analysis according to claim 8, wherein the microorganisms on each of the bio-membranes are cultivated for 24, 48, 72,

Assignee's ref. AU0303015 SUNDIAL's ref. US1206F

SUNDIAL CONFIDENTIAL

and 96 hours, respectively.

13. The method of water analysis according to claim 8, wherein the

concentration of $KMnO_4$ is about 0.02 M (mole per liter).

14. The method of water analysis according to claim 8, wherein the

microorganisms on each of the bio-membrane are stained with KMnO₄ for

about 10 to 30 seconds.

5

* * * * *